



TECHNICAL DATA

102 Barton Street, St. Louis MO 63104
Ph: 800-325-9962 / Fax: 314-865-4107
www.schaefferoil.com

5131 EXTREME MARINE GASOLINE FUEL ADDITIVE

Extreme Marine Gasoline Fuel Additive is a concentrated, multifunctional ashless gasoline additive specially formulated for use in all gasoline and ethanol blends used in high performance marine outboard, personal watercraft, powerboat, sterndrive and inboard engines.

Extreme Marine Gasoline Fuel Additive contains a unique lubricity, detergent, and anti-wear additive package that, when used at the recommended treatment ratio, provides the following premium performance benefits:

- **PERFORMANCE**
 - Helps control/prevent phase separation in ethanol blended gasoline.
 - Increases engine performance and provides smoother idling.
 - Increases fuel lubricity in gasoline, E-10 blended gasoline, and Recreational fuels.
 - Stabilizes the fuel during long term storage.

- **DEPOSIT/CORROSION PROTECTION**
 - Improved carburetor, fuel injector, engine induction system, intake valve and combustion chamber cleanliness.
 - Modification of existing injector deposits, allowing for their removal and safe passage into the combustion chamber where they can be burned.
 - Superb piston deposit control to reduce the risk of engine seizure

- **WEAR PROTECTION**
 - Excellent anti-wear protection of the fuel injectors and fuel pumps.
 - Lubrication of upper cylinders, fuel pumps and injectors.
 - Supplemental ring and valve-train anti-wear protection.

TREATMENT RATIO

1-12ounce bottle treats 50 gallons of fuel

One gallon of Extreme Marine Gasoline Fuel Additive to 500 gallons of fuel

TYPICAL PROPERTIES

Specific Gravity @ 60°F	0.89-0.91
Flash Point °F/°C, Pensky Martin (ASTM D93)	122°-135°/ 50°-57°
Ash Content, % wt. (ASTM D482)	0%
% Nitrogen, % wt	0.3%